


Codici di ordinazione
Order codes

Regolatore
Regulator




CODICE-CODE	REF.
095.01.00006	R 1" 095 04 A
095.01.00005	R 1" 095 08 A

Staffa fissaggio laterale
Side bracket



CODICE-CODE	PRODUCT
C95.01.00018	

Kit di staffaggio
Wall fixing kit



CODICE-CODE	PRODUCT
C95.01.00015	R

Tappo 1/4"
1/4" plug



CODICE-CODE	VERSION
A95 01 00030	GAUGE CONNECTION

Regolatore

- * Stabilità della pressione regolata indipendentemente dalle variazioni a monte.
- * Grande portata con basse perdite di carico.
- * Pomello con dispositivo di bloccaggio della regolazione.
- * Possibilità di fissaggio a parete utilizzando le staffe predisposte.
- * Campi di pressione: 0÷4 Bar, 0÷8 Bar.
- * Pressione massima d'ingresso: 12,5 Bar (1,25 MPa).
- * Temperatura ambiente max (a 10 bar) 50 °C (122 °F).
- * Coppia di serraggio max. inserti G1" IN-OUT: 80 N-m.
- * Portata di riferimento (P=6,3 Bar - Δp=1 Bar): 225 NI/min (acqua).
- * Peso: 1,721 Kg.
- * Prodotto conforme alla direttiva 2002/95/CE (RoHS).
- * Coppia serraggio manometro: 10 Nm.

Regulator

- * Sensitive high performance model.
- * High flow rate with low load losses.
- * Lockable safety knob.
- * Can be wall mounted using the relative brackets.
- * Pressure ranges: 0÷4 Bar, 0÷8 Bar.
- * Maximum inlet pressure: 12,5 Bar (1,25 MPa).
- * Max. ambient temperature (at 10 bar) 50 °C (122 °F).
- * Max. torque inserts G1" IN-OUT: 80 N-m.
- * Reference flow rate (P=6,3 Bar - Δp=1 Bar): 225 NI/min (water).
- * Weight: 1,721 Kg.
- * Product complies with Directive 2002/95/CE (RoHS).
- * Max torque gouge port: 10 Nm.

